

DARASET® 300

Chloride-free, set accelerator based on nitrate
Set accelerating admixture for concrete according to
EN 934-2:T6

Product Description

DARASET 300 is liquid set accelerating admixture for concrete and mortar.

Mode of Action

DARASET 300 shortens the setting time of concrete, compensates for the set-slowing effects of cooler weather conditions, and contributes to the development of higher early strengths.

DARASET 300 can be used at temperatures above -15°C .

The constituent materials should be heated, and the temperature of the fresh concrete should be higher than $+10^{\circ}\text{C}$.

Only non-frozen aggregates should be used. The substrate, rebar, and molds should also not be frozen, and the concrete must be protected against frost.

Dosage and Special Information

Best results are obtained when added with the gauging water, or as the last component of the mix, and then mixed for a minimum of an additional 45 seconds.

Preliminary tests according to official national standards are always required before use!

Never pre-mix DARASET 300 with any other admixture before they are dosed into the concrete!

Status: 07/13

Typical Properties

Form	Fluid
Colour	Yellowish
Density	approx. $1.42 \pm 0.03 \text{ g/cm}^3$
pH Value	8.5 ± 1.0
Total chloride content	$< 0,10 \text{ m.-%}$
Alkali content	$< 5,0 \text{ m.-%}$
Storage	Keep original containers closed, protect from excessive heat and frost. Once frozen, material cannot be used.
Recommended Dosage	$0.50\text{--}3.00 \text{ m.-%}$ by cement mass
Physiological effect	May irritate skin and eyes: See Safety Data Sheet
Shelf life	approx. 1 year in closed original containers

gcpat.com | T +49 (0) 52 81 77 04 -0 | F +49 (0) 52 81 77 04 -99

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

OPTEC is a trademark, which may be registered in the United States and/or other countries, of GCP Applied Technologies Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2016 GCP Applied Technologies Inc. Alle Rechte vorbehalten.

GCP Applied Technologies Inc., 62 Whittemore Avenue, Cambridge, MA 02140 USA

Pyrmonter Straße 56 32676 Lügde

GCP0082_DARASET-300_GB_DE_0917 al